

Claims

- 5 1. A digital amplifier including a noise shaper and a dither generator arranged to introduce noise to the shaper, said generator using a seed value derived from a state variable of said shaper.
2. A digital amplifier as claimed in claim 1 and wherein the number of bits in the generated noise exceeds that of the seed value.
- 10 3. A digital amplifier as claimed in Claim 1 or Claim 2 and wherein the dither generator includes shift registers of predetermined bit lengths to receive said seed values and provide a noise output.
- 15 4. A digital amplifier as claimed in any preceding claim including means for scaling said noise.
5. A digital amplifier including a clocked modulator wherein clock activity is monitored by counting divided multiples of the clock.
- 20 6. A digital amplifier as claimed in claim 5 and including multiple clocks and wherein a first clock is used to count a second clock.
7. A digital amplifier as claimed in claim 6 and wherein a divided multiple of said second clock is counted.
- 25 8. A digital amplifier as claimed in any of claims 5 to 7 and wherein output is disabled when a clocking error is detected.
- 30 9. A digital amplifier as claimed in any of claims 5 to 8 and wherein when a clocking error is detected, a parameter indicative of the error is stored.

10. A digital amplifier having a detection arrangement to provide an error signal when there is no modulator drive or clock loss or undefined input states to an h-bridge leg.
- 5
11. A digital amplifier having a deadtime generation or control arrangement substantially as herein described.
12. A digital amplifier in which deadtime is balanced on rising and falling edges of signals.
- 10
13. A digital amplifier in which deadtime is adaptive to gate charge of the output switching device.
- 15
14. A digital amplifier in which deadtime is temperature independent or temperature compensated.
15. A digital amplifier having programmable deadtime control or inter-channel delay or ABD delay which may be optimized by means of programming registers.
- 20
16. A digital amplifier as claimed in claim 15 and wherein deadtime is controlled by a resistor or programming register.
- 25
17. A digital amplifier substantially as herein described.
18. The features hereof in any novel or inventive combination.
19. A digital amplifier including means for reducing the effect of peak or spike voltages from the power supply.
- 30

20. A digital amplifier as claimed in claim 19 and wherein said means comprises a clamp diode in association with power supply filtering.

21. An integrated half bridge device laid out substantially as herein described.

5

22. An integrated half bridge device with pin out substantially as herein described or equivalent thereto.

10

23. A digital amplifier having high side over current protection substantially as herein described.

24. A digital amplifier in which the layout and design of the reclocker substantially herein described.